




3960 lbs



8'6" - 27'11"



6'5" - 10'4"

	4850 lbs	-	2T-D7: 22 lbs	JIB600M: 220 lbs	
	10'2"x2'7"x6'6"		0.62 MPH		20°
	4188 lbs		901 PSF		
	3kW 24V-DC SEP n°4 6V- 420 Ah				
	120V-20A				
<p>Telescopic Boom: 1 base and 4 telescopic sections high-tensile structural steel. All sections synchronized and full power. Braccio Telescopico: 1 braccio principale e 4 telescopici in acciaio strutturale ad alta resistenza. Sfilo completamente idraulico e sincronizzato. Teleskopausleger: 1 Hauptausleger + 4 Hochwiderstand Stahl Teleskopausleger. Voll hydraulischer und teleskopierbarer Ausleger. Pluma Telescópica: 1 pluma principal y 4 telescópicas en acero de alta resistencia. Elementos sincronizados e hidráulicos. Flèche Téléscopique: 1 flèche principale et 4 téléscopiques en acier à haute résistance. Eléments synchronisés et hydrauliques.</p>					
	360° 1.5 rpm		0°/70° 14"		
	6'11" - 27'11" 26"		1320 lbs - 196' - Ø5/16 in 52 ft/min		

